

AD A109041

DTIC FILE COPY

2

NRL Memorandum Report 4641

LEVEL II

# The Cavity Q for Ergodic Eigenmodes

EDWARD OTT AND WALLACE M. MANHEIMER

*Plasma Physics Division*

December 22, 1981



NAVAL RESEARCH LABORATORY  
Washington, D.C.

DTIC  
ELECTE  
DEC 31 1981  
S D

81 12 30 048

Approved for public release; distribution unlimited.

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM																
1. REPORT NUMBER NRL Memorandum Report 4641	2. GOVT ACCESSION NO. A1-4221	3. RECIPIENT'S CATALOG NUMBER 1112																
4. TITLE (and Subtitle)  THE CAVITY Q FOR ERGODIC EIGENMODES	5. TYPE OF REPORT & PERIOD COVERED Interim report on a continuing NRL problem																	
	6. PERFORMING ORG. REPORT NUMBER																	
7. AUTHOR(s)  Edward Ott* and Wallace M. Manheimer	8. CONTRACT OR GRANT NUMBER(s)																	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Research Laboratory Washington, D.C. 20375	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS J.O. # 47-0896-0-1 P.R. # 01-81ET53020-001																	
11. CONTROLLING OFFICE NAME AND ADDRESS	12. REPORT DATE December 22, 1981																	
	13. NUMBER OF PAGES 8																	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	16. SECURITY CLASS. (of this report) Unclassified																	
	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE																	
16. DISTRIBUTION STATEMENT (of this Report)  Approved for public release; distribution unlimited.		<table border="1"> <tr><td colspan="2">Accession For</td></tr> <tr><td>NTIS</td><td>65a1</td></tr> <tr><td>DTIC</td><td>2.5</td></tr> <tr><td>Unannounced</td><td></td></tr> <tr><td>Justification</td><td></td></tr> <tr><td colspan="2">By</td></tr> <tr><td colspan="2">Date</td></tr> <tr><td colspan="2">A</td></tr> </table>	Accession For		NTIS	65a1	DTIC	2.5	Unannounced		Justification		By		Date		A	
Accession For																		
NTIS	65a1																	
DTIC	2.5																	
Unannounced																		
Justification																		
By																		
Date																		
A																		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)																		
18. SUPPLEMENTARY NOTES  *Laboratory for Plasma and Fusion Energy Studies, University of Maryland, College Park, Maryland.																		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)  Ergodic Eigenfunctions																		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number)  The Q of an overmoded (wavelength much less than cavity size) irregular cavity is calculated by making use of the ergodic theorem.																		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE  
S/N 0102-014-6601

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

254950 elk

## THE CAVITY Q FOR ERGODIC EIGENMODES

We consider here the problem of calculating the  $Q$  of a very overmoded, (wavelength  $\ll$  cavity size) irregularly shaped resonant cavity due to absorption of the electromagnetic radiation at the walls. We assume further that the volume inside the cavity can be either vacuum, or else partially filled with anisotropic inhomogeneous dielectric or plasma. Both the scale length of the dielectric and the radius of curvature of the walls are assumed much larger than the radiation wavelength. However, near the cavity walls, a vacuum is assumed. Our main interest here is in applications concerning magnetically confined plasmas. For instance consider a tokamak containing a hot plasma which radiates at the cyclotron frequency and its harmonics. An important issue is how much of this cyclotron radiation is absorbed by the walls and how much is reabsorbed by the plasma. Generally this can be calculated with a ray tracing code where many rays are followed and the absorption and emission are calculated along each ray path. However if the plasma is optically thin, as it would be at the higher harmonics, and if the reflection coefficient at the wall is near unity the rays would have to be followed for long distances before one could see how much energy is deposited in the wall.

In this paper we utilize the ergodic theorem to calculate the wall absorption for the case where the wave makes many bounces and before it is absorbed. If the local dispersion relation is

$$\omega = F(\underline{k}, \underline{r}) \quad (1)$$

where the  $F$  is real, the ray equations

$$\frac{d\underline{r}}{dt} = \frac{\partial F}{\partial \underline{k}}, \quad \frac{d\underline{k}}{dt} = - \frac{\partial F}{\partial \underline{r}} \quad (2)$$

are relevant. It is evident from Eqs. (2) that the ray equations are a Hamiltonian system for which  $F(\underline{k}, \underline{r})$  plays the role of the Hamiltonian, and  $(\underline{k}, \underline{r})$  are momenta and coordinate variables. Thus Eqs. (2) are subject to the same phenomena of ergodicity onset and ergodic motions of other Hamiltonian systems. Here we consider the case where the solution to Eqs. (2) is ergodic<sup>1,2</sup> with  $F$  the only

Manuscript submitted, August 25, 1981.

constant of the motion of the ray equations. (We note that even in plasma devices, such as tokamaks, where the plasma has a high degree of toroidal symmetry, the conducting walls surrounding the plasma commonly have corrugations and are partly composed of baffles and limiters. Thus this ergodicity assumption is probably well-justified for waves which experience reflections from the walls.) In the case of ergodic ray motions it is expected that the time average over the motion of a wavepacket can be obtained by a phase space average

$$\lim_{\tau \rightarrow \infty} \tau^{-1} \int_0^\tau g(\underline{k}(t), \underline{r}(t)) dt = \int d\underline{k} \int d\underline{r} f(\underline{k}, \underline{r}) g(\underline{k}, \underline{r}) \quad (3)$$

where  $g$  is any function of  $k$  and  $r$  and  $f$  is the microcanonical distribution

$$f(\underline{k}, \underline{r}) = \delta(\omega - F(\underline{k}, \underline{r})) \left\{ \iint d\underline{k} d\underline{r} \delta(\omega - F(\underline{k}, \underline{r})) \right\}^{-1}. \quad (4)$$

On the basis of (4), it is expected that for an eigenmode with resonant frequency  $\omega$  the wave energy density in  $\underline{k}, \underline{r}$  is given by<sup>3</sup>

$$W(\underline{k}, \underline{r}) = \left[ \iint W(\underline{k}, \underline{r}) d\underline{k} d\underline{r} \right] \frac{\delta(\omega - F(\underline{k}, \underline{r}))}{\iint d\underline{k} d\underline{r} \delta(\omega - F(\underline{k}, \underline{r}))}, \quad (5)$$

if the solution of the ray equations is ergodic. This is analogous to the microcanonical ensemble in statistical mechanics where all phase space points on the energy surface (analogous to the constant  $F(\underline{k}, \underline{r})$  surface) are equally likely. In writing Eqs. (4) and (5) we have in mind a cavity filled with a magnetized plasma or anisotropic dielectric. Also we consider only electromagnetic waves which propagate freely from the vacuum into the plasma and visa versa. In this case the two polarizations of plane electromagnetic waves propagating in a given direction, with given frequency are, in general, non-degenerate. That is they have different values of  $|\underline{k}|$ . Thus the dispersion relation  $\omega = F(\underline{k}, \underline{r})$  will possess these two solutions. Hence in this case, Eq. (5) automatically gives the distribution of energy in the two polarizations. In the case of an unmagnetized plasma, isotropic dielectric or vacuum, the two independent polarizations are degenerate, that is, they have the same value of  $|\underline{k}|$ . In this case we supplement Eq. (5) with the information that both polarizations are equally likely. One expects that Eq. (5) holds in the limit of  $k \rightarrow \infty$ ; however, it is not yet known how good Eq. (5) is for finite  $k$ . In this respect, recent numerical experiments are of interest<sup>4</sup> (typically  $kL \sim 10$  in these experiments where  $L$  is a scale length). We shall be interested in applying Eq. (5) in cases where the wave experi-

ences absorption at the conducting boundaries upon reflection. Under these circumstances, we require the following two conditions for the validity of Eq. (5). *Condition A:* The wall absorption in following a typical ray must be slow enough that the ray wanders over a representative region of the  $F(\underline{k}, \underline{r}) = \text{constant}$  surface before significant absorption takes place. *Condition B:* The dispersion relation  $F(\underline{k}, \underline{r})$  must not exhibit any resonances (i.e., solutions with  $k \rightarrow \infty$ ). Condition B is necessary in order that the integral in the denominator of Eq. (4) be finite.

We now calculate the damping of an ergodic eigenmode due to finite wall conductivity. The  $Q$  of the cavity is defined as

$$Q = \frac{\omega \iint W(\underline{k}, \underline{r}) d\underline{k} d\underline{r}}{\oint \eta_s |\underline{J}_s|^2 d^2r} \quad (6)$$

where  $\eta_s$  is the surface skin resistivity  $\eta_s = (\mu_0 \omega / 2\sigma)^{1/2}$ ,  $\sigma$  is the wall conductivity which may be a function of position on the wall,  $\underline{J}_s$  is the rms surface current density vector, and the integral,  $\oint \eta_s d^2r$ , is taken over the boundary of the cavity. Here we wish to calculate  $|\underline{J}_s|^2$  (and hence  $Q$ ).

We recall that, by assumption, near the cavity walls the plasma density is zero. In this region  $F(\underline{k}, \underline{r}) = |\underline{k}|c$ , where  $c$  is the speed of light, and from Eq. (5)  $W(\underline{k}, \underline{r}) \sim \delta[\omega - |\underline{k}|c]$ . Thus, near the walls,  $W(\underline{k}, \underline{r})$  is independent of  $\underline{r}$  and the direction of  $\underline{k}$ . To treat this case we recall that  $\lambda \ll L$  and consider a plane wave in vacuum which is incident on a plane conductor. We also assume, as mentioned previously, that in the vacuum region near the wall  $W(\underline{k}, \underline{r})$  is the same for each of the two independent polarizations. Let  $\theta$  be the angle of incidence, and  $\phi$  the angle that the magnetic field vector  $\underline{H}$  makes with the plane of incidence. Then, from Maxwell's equations and the condition that  $\underline{E}$  tangential vanish, the current  $\underline{J}_s$  created by this plane wave is

$$\underline{J}_s = 2H \cos\phi \underline{\alpha} + 2H \sin\phi \cos\theta \underline{\beta} \quad (7)$$

where  $\underline{\alpha}$  and  $\underline{\beta}$  are unit vectors in the surface of the conductor, respectively perpendicular to and in the plane of incidence. Averaging over  $\phi$  and the solid angle of the incident waves we have that

$$|\underline{J}_s|^2 = \int_0^{2\pi} \frac{d\phi}{2\pi} \int \frac{d\Omega}{2\pi} [4H^2(\cos^2\phi + \sin^2\phi \cos^2\theta)] \quad (8)$$

where  $d\Omega = 2\pi \sin\theta d\theta$ , the integral over  $d\Omega$  is from  $\theta = 0$  to  $\theta = \pi/2$  (i.e., only over incident waves), and  $H^2$  may be related to the average energy density of the eigenmode in the vacuum near the wall

$$\frac{1}{2}\mu_0 H^2 = \iint W(\underline{k}, \underline{r}) d\underline{k} d\underline{r} \frac{V \int \delta[\omega - |\underline{k}|c] d\underline{k}}{\iint \delta[\omega - F(\underline{k}, \underline{r})] d\underline{k} d\underline{r}} \quad (9)$$

where  $V$  denotes the volume enclosed by the cavity. From Eq. (8),  $|J_s|^2 = 4/3 H^2$ . Thus

$$Q = \frac{3\mu_0 c^3}{16\pi\omega \oint \eta_s d^2r V} \iint \delta[\omega - F(\underline{k}, \underline{r})] d\underline{k} d\underline{r}. \quad (10)$$

For vacuum,  $F(\underline{k}, \underline{r}) = |\underline{k}|c$  and Eq. (10) yields  $Q = [3\mu_0\omega] [4 \oint \eta_s d^2r]^{-1}$  where the two independent polarizations have been taken into account.

Similar arguments to those above can be applied to Helmholtz equation in two dimensions ( $x$  and  $y$ ),  $\nabla^2\psi + k^2\psi = 0$  with the eigenfunction zero on the boundary with the result that

$$\langle (\partial\psi/\partial\eta)^2 \rangle = k^2 \int \psi^2 dx dy / \int dx dy, \quad (11)$$

where  $\partial/\partial\eta$  denotes the normal derivative, and  $\langle \dots \rangle$  denotes the average over the boundary. This expression has been checked in numerical experiments by McDonald and Manheimer<sup>5</sup> using the model of Ref. 6. Reasonable agreement was obtained, thus giving an indication of the correctness of our approach. To obtain (11) consider a plane wave of amplitude  $\tilde{\psi}$  incident on a planar boundary where  $\psi = 0$ . This leads to a normal derivative of  $\psi$  at the boundary of amplitude  $2\tilde{\psi} k \cos\theta$ , where  $\theta$  is the angle of incidence. Averaging  $(2\tilde{\psi} k \cos\theta)^2$  over  $\theta$  for incident waves ( $0 \leq \theta \leq \pi/2$ ) then yields Eq. (11).

If the wave has non-zero damping rate  $\gamma(\underline{k}, \underline{r})$  in the plasma then the cavity  $Q$  is  $(Q_w^{-1} + Q_p^{-1})^{-1}$  where  $Q_p$  is the  $Q$  resulting from absorption in the plasma and  $Q_w$  is given by Eq. (10). Thus the fraction of energy absorbed by the wall is  $Q_p(Q_p + Q_w)^{-1}$ . The  $Q$  resulting from the plasma losses is

$$Q_p = \frac{\omega}{2\bar{\gamma}}. \quad (12)$$

where<sup>2</sup>

$$\bar{\gamma} = \frac{\iint d\mathbf{k} d\mathbf{r} \gamma(\mathbf{k}, \mathbf{r}) \delta(\omega - F(\mathbf{k}, \mathbf{r}))}{\iint d\mathbf{k} d\mathbf{r} \delta(\omega - F(\mathbf{k}, \mathbf{r}))}. \quad (13)$$

This may be useful in calculating the amount of energy emitted by cyclotron radiation which is absorbed by the wall in a thermonuclear fusion device.

#### ACKNOWLEDGMENT

This work was supported by the U.S. Department of Energy.

#### REFERENCES

1. Ergodic ray trajectories in plasmas have also been considered elsewhere [J.-M. Wersinger, E. Ott and J.M. Finn, Phys. Fluids 21, 2263 (1978); E. Ott, B. Hui and K.R. Chu, Phys. Fluids 23, 1031 (1980); P.T. Bonoli and E. Ott, Phys. Fluids (to be published); E. Ott and W.M. Manheimer, Bull. Am. Phys. Soc. 25 (8), 988 (1980)].
2. E. Ott, Phys. Fluids 22, 2246 (1979); E. Ott in *Long Time Prediction in Dynamics*, edited by W. Horton, L. Reichl and V. Szebehely (Wiley, New York, to be published).
3. A. Voros in *Stochastic Behavior in Classical and Quantum Systems*, Lecture Notes in Physics 93, Volta Memorial Conference, 1977, edited by G. Casati and J. Ford (Springer-Verlag, Berlin, 1979); M.V. Berry, J. Phys. A 10, 2083 (1977).
4. S.W. McDonald, A.N. Kaufman and M.V. Berry, Bull. Am. Phys. Soc. 24 (8), 942 (1979); J.S. Hutchinson and R.E. Wyatt, Chem. Phys. Lett. 72, 378 (1980); D.W. Noid, M.L. Koszykowski and R.A. Marcus, J. Chem. Phys. 71, 2864 (1979).
5. S. McDonald and W.M. Manheimer, Bull. Am. Phys. Soc. 25 (8), 988 (1980); and to be published.
6. S.W. McDonald and A.N. Kaufman, Phys. Rev. Lett. 42, 1189 (1979).

# DISTRIBUTION LIST

DOE  
P.O. Box 62  
Oak Ridge, Tenn. 37830

UC20 Basic List (116 copies)  
UC20f (192 copies)  
UC20g (176 copies)

NAVAL RESEARCH LABORATORY  
Washington, D.C. 20375

Code 4700 (26 copies)  
Code 4790 (150 copies)

DEFENSE TECHNICAL INFORMATION CENTER  
Cameron Station  
5010 Duke Street  
Alexandria, VA 22314 (12 copies)